



RT-6

APPLICATIONS:

Auto heater tubing, Ventilating ducting,
Automotive exhaust, Moderate suction lines,
Dust collecting Ducting, Refrigeration tubing
armor, Air Blower ducting, Wiring conduit,
Carburetor air intake.

SIZE RANGE:

3/16" to 6" I.D. inclusive.

Other sizes may be available - please contact
the Factory for more information.

CONSTRUCTION:

Fully interlocked

METALS:

Stainless Steel, Galvanized Steel, Brass, Bronze,
and Monel

METAL THICKNESS:

.010 inches - .012 inches

TEMPERATURE RATING

Galvanized Steel: Up to 200C/392F

T304 Stainless Steel: Up to 454C/850F

Nominal I.D. (Inches)	Nominal O.D. (Inches)	Minimum Inside Bend Diameter (Inches)	Weight Foot "100" Feet
3/16	0.281	3.000	11.000
1/4	0.375	3.000	11.000
3/8	0.500	4.000	14.000
1/2	0.625	6.000	16.000
5/8	0.750	6.500	18.000
3/4	0.875	6.500	20.000
7/8	1.000	7.000	24.000
1	1.130	7.500	28.000
1 1/8	1.260	8.500	32.000
1 1/4	1.380	9.500	36.000
1 3/8	1.510	10.000	38.000
1 1/2	1.650	11.000	48.000
1 5/8	1.780	12.000	52.000
1 3/4	1.900	13.000	58.000
1 7/8	2.030	14.000	60.000
2	2.160	15.000	66.000
2 1/8	2.280	15.500	72.000
2 1/4	2.410	16.500	76.000
2 3/8	2.530	17.500	81.000
2 1/2	2.660	18.500	85.000
2 3/4	2.910	20.000	93.000
2 7/8	3.030	21.000	97.000
3	3.160	22.000	102.000
3 1/4	3.410	24.000	110.000
3 1/2	3.660	26.000	118.000
3 3/4	3.910	27.000	127.000
4	4.160	29.000	135.000
4 1/2	4.660	33.000	152.000
5	5.170	37.000	168.000
6	6.170	44.000	200.000

Numbers based on strip thickness of .010" - .012"

Specifications for other sizes not shown and are available on application.